



i2369V



Cabinet Color	Glossy Black Bezel, Base; Hairline texture on Bottom Back Cover	
Panel	TFT Active Matrix LCD, LED Backlight, IPS Panel 23" Widescreen, 16:9 Aspect Ratio 23" Viewable Image Size, Diagonal	
Pixel Pitch	0.265(H) x 0.265(V)mm	
Display Area	509.184(H) x 286.416(V)	
Brightness	250 cd/m2 (typ)	
Contrast Ratio	50,000,000:1 (dynamic)	
Response Time	5ms	
Viewing Angle	Horizontal: 178 Degrees (CR>10) Vertical: 178 Degrees (CR>10)	
Scanning Frequency	Horizontal: 30K~83KHz Vertical: 50~75 Hz	
Pixel Frequency	170MHz	
Maximum Resolution	1920x1080x60Hz	
Recommended Resolution	1920x1080@60Hz	
Supported Resolutions	640x480@60/72/75Hz	720x400@60/70Hz
	800x600@56/60/7/75Hz	832x624@75Hz
	1024x768@60/70/75Hz	1280x720@60Hz
	1280x960@60Hz	1280x1024@60/75Hz
	1440x900@60Hz	1680x1050@60Hz
	1920x1080@60Hz	
Color	16.7M	
Signal Input	Analog: 0.7Vp-p(standard), 75 OHM, Positive	
Digital Input	DVI with HDCP*	
Connectors	Analog RGB Signal: 15-pin D-sub Male Digital Signal: 24-pin DVI	
Power Source	Universal 100~240VAC, 50/60Hz	
Power Consumption	On: 28 Watts (typical), Standby: <0.5W	
Plug & Play	DDC/2B, DDC/CI	
User Control	Left/Clear Vision, Right/Image Ratio, Source/Auto/Exit, Menu/Enter, Power	
OSD Languages	16 Languages including English, French and Spanish	
Regulations	FCC, cCSAus, CE, TUV/S, EPA Energy Star	
Other Features	Extra slim, Framless, IPS panel, User Friendly Graphical OSD Menu, Includes AOC's e-Saver, Screen+ and iMenu Software, VESA 75mm Wall Mount Compliant*, Windows 8 compatible	
Dimensions (WxHxD mm)	Monitor: 531.4x398x204 , Carton: 603x467x138	
Dimensions (WxHxD inches)	Monitor:20.9x15.7x8.0 , Carton: 23.7x18.4x5.4	
Weight	8.4 lbs (3.8 Kg) Net 12.1lbs (5.5 Kg) Gross	
Loading Qty w/pallet	20' = 620 pcs.; 40' Std = 1302 pcs.	
UPC Code	685417060887	

Note: Specifications are subject to change without notice. *High-bandwidth Digital Content Protection: Enables viewing of High-Definition contents.
A02/13