MC362dn Specifications





With colour print speeds of 22ppm and mono print speeds of 24ppm, the MC362dn is perfect for small businesses or workgroups providing a variety of functions and a flexibility of printing, scanning, copying and faxing in-house. Managing your internal documents and those you receive, allows you to work smarter and manage your document flow throughout your business or workgroup.

The MC362dn is built on tried and tested technology that your business can rely on to deliver over and over again.

Outstanding features to support your business needs

- Automatic Duplex printing, copying, scanning and faxing as standard with colour print speeds up to 22ppm
- 50-sheet Reverse Automatic Document Feeder for quick and easy copying and scanning double-sided documents
- Time to first print, 9 seconds colour, 8.5 seconds mono
- Intuitive menus and controls with one touch function buttons and 3.5" LCD display for simple user interface
- Print directly from or scan directly to a USB stick

Outstanding print quality and media flexibility

- Duplex as standard (up to 176gsm), for in-house professional printing
- ProQ2400 multi-level output quality, 1200 x 600dpi print resolution
- Microfine High Definition toners for superb print quality
- Flexible media handling: from A6 to 1320mm banners; card stock up to 220gsm
- OKI Template Manager makes it easy to format and print various documents in-house

Functionality to improve your productivity and workflow

- High quality, copying, scanning and faxing using LED digital technology
- Overlay function enables you to save logos or forms in the MFP's memory, for re-use in other documents
- Super G3 speed fax for high speed delivery and receipt
- Send faxes over the internet
- Fast scan speed of up to 20ppm colour and 30ppm mono
- LDAP direct access to contact and email data from an existing server directory


- USB and network TWAIN scanning (PC and Mac)
- ID card copying for simple copying of double sided ID cards on a single sheet
- Document collation automatically sorts copies of multi-page documents

Efficient and cost saving functionality

- Eco Mode improves throughput performance and reduces energy consumption
- Deep Sleep Mode reduces energy consumption to less than 1.5W
- OFF mode automatically powers down from Deep Sleep, reducing energy consumption to 0.5W when not in use
- Free consumables recycling programme

Useful utilities that help you control and manage your printing

- PrintSuperVision helps you control and resolve issues with printers across your networks
- Print Job Accounting provides visibility and control of your organisation's print spend across your network





MC362dn - Colour and Mono Multifunction Product

Printer		Typefaces	
A4 Print speed	22ppm colour, 24ppm mono	Duintou fonto	Scalable: 87 PCL Fonts and 80 PostScript fonts; PCL Bitmap
Time to first print	9 seconds colour, 8.5 seconds mono	Printer fonts	fonts: Lineprinter OCR-A/B, USPS ZIP Barcode
Warm up time	Up to 60 seconds from power on and up to 32 seconds from power save	Barcode	12 types of one dimension with 28 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4POSTNET, Customer barcode; 1 type of two dimension: PDF417
Processor speed	533MHz		
SCANNER		PRINT QUALITY	
Optical Resolution	-	Resolution	ProQ2400 Multi-level Technology, 1200 x 600dpi, 600 x 600dp
Speed		Enhancements	Auto Color Balance, Photo Enhance via driver
Colour depth			(excludes PostScript driver)
Document input	50-sheet Reverse Automatic Document Feeder (RADF), flatbed scanner	PAPER HANDLING	
Contrast		Paper capacity	Tray 1: 250 sheets of 80gsm; Multi-purpose tray: 100 sheets
Format			of 80gsm; RADF: 50 sheets of 80gsm
	LDAP, 100 E-mail address, 20 group addresses	Paper capacity optional 2nd tray	530 sheets of 80gsm
	FTP, HTTP, USB memory, E-mail, TWAIN, CIFS	Maximum paper capacity	880 sheets of 80gsm
	, , , ,	махінішіі рареі сарасіту	•
Сору			Tray 1: A4, A5, B5, A6; Tray 2: A4, A5, B5; Multi-purpose tray: A A5, B5, A6, Envelopes (C5, DL, Com-9, Com-10, Monarch), Index
First copy out	Less than 14 seconds colour, less than 12 seconds mono	Paper sizes	
Speed	Up to 22cpm colour and up to 24cpm mono		
Resolution	Up to 600 x 600dpi		0 ,, 1 ,, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1
Reduction / Enlargement	Zoom 25-400%	Paper weight	Tray 1/2: 64 to 176gsm; Multi-purpose tray: 64 to 220gsm; Duplex: 64 to 176gsm; RADF: 60 to 105gsm
Maximum copies	99	Duplex	Standard
	•		Face Down: 150 sheets of 80gsm; Face Up: 100 sheets of 80gsm
FAX		_	
Connectivity	RJ11 x 2 (Line/Tel), PSTN, PBX Line	GENERAL FEATURES	1
Speed	ITU-T G3(Super G3) up to 33.6kbps, 3 seconds/page	Memory	
Fast dialing	16 one touch dials (8 x 2 using shift key), 100 speed dials	-··	Operating temperature/ humidity: 10°C to 32°C (17°C to 27°C recommended)/ 20% to 80% RH (50% to 70% RH recommended)
Groups	Up to 20	Environment	Storage temperature/ humidity: -10°C to 43°C/ 10% to 90% Rh
Broadcast	Maximum 100	Power supply	<u> </u>
	4MB (approx. 200 pages transmit and receive)	Power consumption	Typical: 500W: Max: 1170W: Idle: 100W: Power Save: (20W:
OPERATOR PANEL LCD Panel	Single simplified blue backlit graphics panel: 84.1mm (W) x 33.6mm (H); Resolution: 320x128 dots	Noise level	Power save: Inaudible
Key pad	12 alpha/numeric keys, 4 main function buttons (Copy, Scan, Print, Fax), Color & Mono Start, Status, Setting, Help, One Touch & Shift keys, 6 main navigation buttons (Back, Up, Down, Left, Right, OK), Clear, Stop, Power Save, Reset/Log Out	Dimensions (HxWxD)	444 x 427 x 509mm
		Weight ⁴	<29kg approx
		Duty cycle	Maximum: 45,000 pages/month; Recommended: Up to 3,000 pages/month
INTERFACE AND SOFTWARE	1	Warranty	<u>'</u>
Connectivity	10/100 TX Ethernet, USB 2.0 Device IF, USB 2.0 Host IF	Product order number	MC362dn: 44952104
•	PCL6 (XL3.0), PCL5c, PostScript 3 emulation,	Accessories (Order Numbers)	
Printer languages	SIDM (IBM-PPR, EPSON-FX)	2nd paper tray	1
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IPv4&v6, SMTP, POP3, HTTP, SNMPv1&v3, DHCP, DNS, LPR, Port9100, BOOTP, ARP, FTP, CIFS, LDAP, SLP, Bonjour. NetWare, EtherTalk, NetBEUI, LLTD, Web Service on Devices		01314101
			256MB: 01182907; 512MB: 01182908
		Consumables (Order Numbers)	
OS Compatibility ¹	Windows XP (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Vista (32-bit & 64-bit) / Windows 7 (32-bit & 64-bit); Mac OS X 10.3.9 to 10.7	Toner cartridge* (3,500 pages)	Black: 44469803
		Toner cartridges* (2,000 pages)	Cyan: 44469706; Magenta: 44469705; Yellow: 44469704
Advance 1 of 11		Image drum**	44968301
Advanced networking & security		Transfer Belt (60,000 pages)	
Utility suite ¹	Template Manager ² , Color Correct, OKI LPR ² , Color Swatch Utility ² , PrintSuperVision.net ² , PrintJob Accounting Server ² , Print Job Accounting Server ² , Print Job Accounting Client, Web Driver Installer ² , Network Card Setup, Configuration Tool ² , ICC Color Profiles, PS Gamma Adjuster, Profile Assistant ³ ,	Fuser Unit (60,000 pages)	
	PDF Direct Print ² , Actkey ²	A4 pages.	

A4 pages. **Prum: Average life of 3 pages per job from tray 1 in simplex mode (30,000 pages black, 20,000 pages colour).

 ${}^{1}Check \ local \ OKI \ website for latest \ driver releases \ and \ OS \ compatibility; \ {}^{2}Windows \ only; \ {}^{3}Mac \ only; \ {}^{4}Including \ all \ consumables$

Document management Nuance PaperPort SEv11, Nuance OmniPage SEv16

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

OKI SYSTEMS (POLSKA) Sp. z o.o.

Domaniewska str. 42 02-672 Warsaw Poland

Tel: +48 22 44 86 500 Fax: +48 22 44 86 501

www.okiprintingsolutions.com

